

METRIC-ISO 5821 STANDARD CAP ELECTRODES











T.J. Snow Co. • (423) 894-6234 • FAX (423) 490-2417 • Authorized Distributor CMW Inc.

These economical, quick change caps are made of long-lasting, highly-efficient Class 2.18150 copper alloy, precision manufactured to exact tolerances in a wide range of standard configurations or to your special requirements.






CMW FEMALE METRIC-ISO 5821 CAP ELECTRODES

ALL DIMENSIONS MARKED WITH AN (*) ARE COMMON TO EACH CAP IN A HORIZONTAL LINE.

	 METRIC TYPE (A)	 METRIC TYPE (B)	 METRIC TYPE (C)	 METRIC TYPE (D)
Taper 1:10 Dia. 13mm (.512)* Length 18mm (.709)* Class 2.18150	 MPF241Z-01	 MPE241Z-01	 MPC241Z-01	 MPD241Z-01
Taper 1:10 Dia. 16mm (.625)* Length 20mm (.787)* Class 2.18150	 MPF25Z-01	 MPE25Z-02	 MPC25Z-02	 MPD25Z-02

CMW FEMALE METRIC-ISO 5821 CAP ELECTRODES

ALL DIMENSIONS MARKED WITH AN (*) ARE COMMON TO EACH CAP IN A HORIZONTAL LINE.

	 METRIC TYPE (E)	 METRIC TYPE (F)	 METRIC TYPE (G)
Taper 1:10 Dia. 13mm (.512)* Length 18mm (.709)* Class 2.18150	 MPA241Z-01	 MPB241Z-01	No Standard Available
Taper 1:10 Dia. 16mm (.625)* Length 20mm (.787)* Class 2.18150	 MPA25Z-03	 MPB25Z-03	 MPA25Z-09